ICBA Platinum Edition, CE 220-240V

Height: 26.8" Width: 10.2" Depth: 22.1" (68.1cm) (25.9cm) (56.1cm)



- 4.3" Color Touchscreen aides in customizing recipes, brewing options and control
- The Infusion Series® Platinum Edition relies on the powerful duo of the Peak Extraction Sprayhead and SmartWAVE® technology to further enhance the uniformity of extraction and resistance to limescale buildup.
- USB programming for uploading and downloading recipes and software updates, all in less than a minute
- Brews into 2.5 to 3.8L (84 to 128 oz) airpots and 3.8 to 5.7L (1 to 1.5 gallon) baseless Thermofresh servers
- BUNN Infusion Series technology allows for multiple recipes from one footprint
- Energy-saver mode reduces tank temperature during idle periods
- Electronic funnel lock prevents removal of the brew funnel until drip- through is complete
- · Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing
- Hot water faucet (supplied for custom installation)



Agency:



Specifications

Funnel Locks Faucet: Variable

Water Access: Plumbed Sprayhead: Silicone-17Holes

Finish: Stainless

Funnel: Stainless Steel

Additional Features

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr Input H²O 236ml cups/hr Temp.		Phase	# Wires plus Ground	Hertz	
220-240	11.0-12.0	2400-2900	Yes	EURO 16A	141	60°F (15.5°C)	1	2	50-60	

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/208V or 120/208V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
PSI	kPa	Fitting Supplied	Water Flow Required (GPM) 1.00				
20-90	138-621	3/8" Male Flare Fitting					


CAD Drawings

2D	Revit	KLC		

MARNING:







	Unit				Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume		
English	26.8 in.	10.2 in.	22.1 in.	34.9 in.	13.3 in.	27.4 in.	53.710 lbs	7.321 ft³		
Metric	68.1 cm	25.9 cm	56.1 cm	88.6 cm	33.7 cm	69.5 cm	24.363 kgs	0.207 m³		




Related Products & Accessories: ICBA Platinum Edition, CE 220-240V(53300.0500)

























Serving & Holding Options: ICBA Platinum Edition, CE 220-240V(53300.0500)



AIRPOT, 2.5L GL PB 6/ CASE

Product #:13041.0101



AIRPOT, 2.5L SST LA SINGLE PK

Product #:32125.0000



AIRPOT, 2.5L SST LA 6/ CASE

Product #:32125.0100



AIRPOT, 3.0L SST LA SINGLE PK

Product #:32130.0000



AIRPOT, 3.0L SST LA 6/ CASE

Product #:32130.0100



AIRPOT, 3.8L SST LA SINGLE PK

Product #:36725.0000



AIRPOT, 3.8L SST LA 6/ CASE

Product #:36725.0100



STAND ASSY, TF SERVER

Product #:39795.0003



TF SERVER, DSG2 1G SST NOBASE

Product #:42700.0050



TF SERVER, DSG2 1G BLK NOBASE

Product #:42700.0051



TF SERVER, 1G DSG GEN3 NOBASE

Product #:42700.0250



TF SERVER,DSG2 1.5G SST NOBAS

Product #:42750.0050



TF SERVER, 1G/3.8L MECH NOBASE

Product #:44000.0050



TF SERVER, 1G/3.8L MECH BLK NOBASE

Product #:44000.0051



TF SERVER, 1G MECH GEN3 NOBASE

Product #:44000.0250

STAND ASSY, TF SERVER

Product #:54473.0000



STAND ASSY KIT, TF SERVER

Product #:54473.1000

